

AIRTEMP 220

Hot air delivery hose designed for compressors and pneumatic systems like flexible connection between motor blower and road tanker used for dry pellets, abrasive powders and granular material transport.

Hose Construction

Tube: Black, smooth, insulating, EPR rubber compound with very good resistance to high temperature

Reinforcement: Synthetic textile fabrics yarns

Cover: Black (N), smooth, insulating, wrapped finish EPDM rubber compound, resistant to heat, abrasion, ozone and weather



- Wide temperature range
- Insulating hose
- Could be complementary to CERGOM
- Burst Pressure Value 3:1

Tolerances

According to RMA steel mandrel
Refer to Technical Handbook on page TH34

Temperature Range

-40 °C (-40 °F) to +220 °C (+435 °F)

with peaks to +240 °C (+465 °F)

Part Number	I.D. (mm)	O.D. (mm)	Working Pressure			Weight kg/m	min. Bend Radius mm	in Stock
			MPa	psi	bar			
IH36346010/40	51	69	1.0	150.0	10.0	1.85	350	N
IH36346011/40	60	78	1.0	150.0	10.0	2.13	420	N
IH36346012/20	65	83	1.0	150.0	10.0	2.40	455	N
IH36346013/20	75	93	1.0	150.0	10.0	2.62	550	N
IH36346014/20	80	98	1.0	150.0	10.0	2.65	600	N

RUBBER AIR HOSE AIRTEMP 220 °C – MADE IN ITALY

Parker

Distributed by:

DAIS GLOBAL

Bulgaria
Telephone: +359 2 973 27 67
Fax: +359 2 973 26 65
E-mail: office@daisglobal.eu
Web: http://markuchi.eu/

România
Telephone/Fax : +40 21 780 45 58
E-mail: office_ro@opwmarket.com
Web: http://furtunuri.eu/

Srbija
Telephone/Fax : 038111/2619-200
E-mail: office_sr@opwmarket.com
Web: http://creva.eu/