

# CEMENT SM 10

Suitable for suction and delivery of dry cement to road tankers and storage bins or silos.

## Hose Construction

**Tube:** Black, antistatic smooth abrasion resistant BR/NR rubber compound, abrasion max. 60 - 70 mm<sup>3</sup>

**Reinforcement:** Synthetic textile fabrics, embedded steel wire helix

**Cover:** Black, abrasion and weather-resistant, SBR rubber compound








- In-plant transfer/loading, bulk transport trucks
- Construction, general industry
- Good flexibility
- Vacuum 0.8 bar
- Burst Pressure Value 3:1

## Temperature Range

-30 °C (-22 °F) to +70 °C (+158 °F)

## Tolerances

According to RMA steel mandrel  
Refer to Technical Handbook on page TH34

Part Number	 I.D. (mm)	 O.D. (mm)	 Working Pressure			 Weight	 min. Bend Radius	in Stock
			MPa	psi	bar			
IH36923100/40	50	64	0.1	150.0	10	1.92	300	Y
IH36923101/40	60	74	0.1	150.0	10	2.26	360	N
IH36923105/20	75	93	0.1	150.0	10	3.53	450	N
IH36923102/20	100	118	0.1	150.0	10	4.80	600	Y
IH36923109/20	120	140	0.1	150.0	10	6.54	720	N
IH36923107/20	125	143	0.1	150.0	10	5.77	750	N

RUBBER HOSE CEMENT 10 bar MADE IN ITALY



Distributed by:



Bulgaria  
Telephone: +359 2 973 27 67  
Fax: +359 2 973 26 65  
E-mail: office@daisglobal.eu  
Web: http://markuchi.eu/

România  
Telephone/Fax : +40 21 780 45 58  
E-mail: office\_ro@opwmarket.com  
Web: http://furtunuri.eu/

Srbija  
Telephone/Fax : 038111/2619-200  
E-mail: office\_sr@opwmarket.com  
Web: http://creva.eu/