

ASPIREX PU/ANC

Suitable for suction of warm air, abrasion dust, warm fumes, saw-dust, wood-shavings, cement, cereal grains, sugar, and other granules.

Hose Construction

PU transparent and antistatic hose having a grey, rigid PVC spiral, resistant to crush, abrasion and ozone, with antistatic 9 wires copper cord.

Food and beverage – The polyurethane used is in conformity to:

– F.D.A. – CFR 21

parts 175, 105, 177, 1680, 177, 2600;

– CEE

82/711, 85/572, 89/109, 90/128,

92/30, 93/8, 95/3, 98/11

Temperature Range






-25 °C (-13 °F) to +85 °C (+185 °F)



- In conformity with FDA title 21 and multiple EC specs
- Strong abrasion resistance
- Not to be used under pressure
- Vacuum 0.5 bar for ID up to 32 mm then 0.40 bar

Tolerances

Refer to Technical Handbook on page TH34

Part Number	 I.D. (mm)	 Wall (mm)	 Working Pressure			 Weight	 min. Bend Radius	in Stock
			MPa	psi	bar			
IH35576038/20	38	44.6	–	–	–	0.23	45	N
IH35576050/20	50	57.0	–	–	–	0.31	57	Y
IH35576060/20	60	67.4	–	–	–	0.39	67	Y
IH35576080/20	80	89.0	–	–	–	0.61	89	Y
IH35576102/20	102	112.4	–	–	–	0.84	112	Y

Distributed by:



Our locations:

Bulgaria
3, Poruchik Nedelcho Bonchev Str.,
fl. 5 1528 Sofia

Telephone: +359 2 973 27 67
Fax: +359 2 973 26 65
E-mail: office@daisglobal.eu

România
Str. Nicolae Teclu nr.5 , cam.3-7
Sector 3 , 032368 BucureștiB

Telephone/Fax : +40 21 780 45 58
E-mail: office_ro@opwmarket.com

Serbia
Srbija, Krajiška 71a, lok.10, Beograd,
Zemun 11080B

Telephone/Fax : 038111/2619-200
E-mail: office_sr@opwmarket.com