



RADIOR 10

Flexible rubber hose for delivery of hot water in heating and cooling of automotive LPG and methane systems.

Hose Construction

Tube: Black, smooth EPDM nitrosamine free rubber compound
 Reinforcement: Synthetic textile yarns
 Cover: Smooth, black, heat, ageing and weather-resistant EPDM nitrosamine free rubber compound








- Specific for cooling system
- Also used in combination with Autogas ECE 67/110 in CNG/LPG engines
- Robust structure to avoid kinking
- Burst Pressure Value 3:1

Temperature Range

-30 °C (-22 °F) to + 100 °C (+212 °F)
 with peaks +120 °C (+248 °F)

Tolerances

According to UNI EN ISO 1307
 Refer to Technical Handbook on page TH34

Part Number				Working Pressure					in Stock
	I.D. (mm)	O.D. (mm)		MPa	psi	bar			
IH30114029/100	7	13	1.0	150.0	10	0.13	50	N	
IH30114030/50	15	23	1.0	150.0	10	0.35	90	Y	
IH30114030/100	15	23	1.0	150.0	10	0.35	90	Y	

RUBBER HOSE RADIOR 10 bar I.D. mm MADE IN ITALY



Distributed by:



Bulgaria
 Telephone: +359 2 973 27 67
 Fax: +359 2 973 26 65
 E-mail: office@daisglobal.eu
 Web: http://markuchi.eu/

România
 Telephone/Fax : +40 21 780 45 58
 E-mail: office_ro@opwmarket.com
 Web: http://furtunuri.eu/

Srbija
 Telephone/Fax : 038111/2619-200
 E-mail: office_sr@opwmarket.com
 Web: http://creva.eu/