

ROBUR GPL

ROBUR GPL



Working t°

-30 °C ÷ +70 °C

Tolerances

L: ± 1%

Hose construction

Tube: Low diffusion rate seamless extruded NBR rubber compound of uniform thickness.

Reinforcement: Two braids of high tensile steel wire

Cover: Black, SBR/CR rubber compound pin-pricked to prevent the formation of blisters, resistant to abrasion, oils, ozone and weathering

Applications

Liquid gas applications (methane, propane, LPG) in the loading and unloading of tankers and in the service stations.

Number	ID mm	OD mm	WP bar	BP bar	Weight kg	R min mm
IH36520560/0	6,5	16,6	25	1380	0,43	60
IH36520561/0	8	17,7	25	1180	0,45	70
IH36520562/0	9,5	20,2	25	1100	0,56	80
IH36520563/0	13	23,2	25	960	0,68	90
IH36520564/0	16	26,5	25	760	0,80	95
IH36520565/0	19	30,5	25	620	1,03	100
IH36520566/0	25	38,5	25	560	1,41	150
IH36520567/0	32	45,6	25	440	1,82	200
IH36520568/0	38	52	25	340	2,00	280
IH36520569/0	51	66,5	25	320	2,86	350

ROBUR GPL